

GPR1.0


Magnetic clip lamp

LAGO

Robust, with its vertically adjustable beam, magnet and clamp, GPR1.0 is ideal for maintenance applications

MANUAL mode

Wide light beam, with 3 lighting intensities for a power suitable for proximity work.



Uniform wide flow



Long operating time



Strong-power magnet



Weather and dust resistance



Excellent shock and crush resistance



Vertical 180° adjustable beam



Light, holds in hand and pocket

Designer and manufacturer, Lagolight offers solutions of portable lighting for professionals

Not just a lamp, this is a tool



LAGO



GPR1.0 magnetic clip lamp

Lighting

Reference: LG0010

1 Osram super mid-power LED. IRC: 82.
3 lighting intensities (Eco, Mid and Max)

Wide and uniform beam for comfortable lighting of work area and hands:

- 50 lumens in Max intensity, 22 lumens in Mid intensity and 10 lumens in Eco intensity (ANSI FL1 Standard).
- Lighting distance: 25 meters in Max, 18 meters in Mid and 12 meters in Eco (ANSI FL1 Standard).
- Beam diameter: 0.6 meter at a distance of 1 meter.

Vertical 180° adjustable light beam (90° up and 90° down).

Energy – Operating time

3 LR03/AAA 1.5V alkaline batteries supplied.
Operating time: 90 hours in Eco and 18 hours in Max (ANSI FL1 Standard).
Compatible with **DUOPAK** and RC03/AAA 1.2V rechargeable batteries (not supplied).

Application – Use

Industrial maintenance - Construction - Craftsmen (plumbing, electrical...) - Automobile repair...

Magnetizes on any steel surface.

Pinches on any support.

Holds in your hand like a torch.
Stands on a flat surface with beam orientation at 180 degrees.
Operating temperature: -25°C / +50°C.

Protection – Safety

IP54: weather and dust resistant.
Excellent shock and crush resistance. Fall height: 2.0 m.
Rubber protection stripes on both jaws of the clamp and under the magnet.
Security lock on/off: switch-on safety device.
Electronic protection of the lamp in case of short-circuit or polarity reversal.
Attached battery cap; simple and fast battery changing.
LED risk: Group 1, low risk; no risk at a distance of 0.5 meter. Measures under IEC 62471 Standard.

Lamp enclosure

Case in polyamide, resistant to usual workshop solvents, hydrocarbons and chemical products.
High-quality optical polycarbonate glass, with polyurethane rubber coating.
Electrical contacts: stainless steel. Maintenance: rinse the lamp with clear water and dry.

Weight – Dimensions

Extremely light weight: 108 grams, batteries included.
Maximum clamp opening: 36 mm.
Dimensions: 93x62x54 mm. Case color: blue.
Customizable on request (color, marking...).

Accessories (optional)

DUOPAK, rechargeable Lithium USB-C battery pack.

Warranty

Warranty: 5 years.
All products are tested during production and before packaging.

LAGOLIGHT
Headlamps & Portable lighting

531 route des Vernes - Pringy - 74370 Anney - France
+33 (0)4 50 60 55 92 contact@lagolight.com
www.lagolight.com

Designer &
manufacturer
for
30 years