

LPR3.0

Chest lamp

# LAGO


With its reflective harness, the LPR3.0 chest lamp is real safety equipment complementary to torches and headlamps

**VARIO Mode**

Fine adjustment of the lighting intensity: choose the power that's right for you.

**Multi Beam**

3 lighting beams: XXL large for close-up work, focused for remote inspections and focused and XXL large handset for quick trips.



Powerful light flow



Excellent operating time



Light weight



Weather and dust resistant



High impact and crush resistance



Beam swiveling up and down



Battery test mode



Harness with reflective stripes

Designer and manufacturer, Lagolight offers solutions of portable lighting for professionals



Not just a lamp, this is a tool



## Chest lamp **LPR3.0**

### Lighting

Reference: LP0030

2 Osram high-power white LED. IRC: 72. 5000K.

VARIO progressive lighting dimmer on the 3 beams, with memory of the last setting.

**Combined focused and wide beams** for moving with illumination of the near area and perspective in the distance:

- 251\* lumens in VARIO max, 6\* lumens in VARIO min.
- Lighting distance: 75\* meters in VARIO max.



MODE  
MOVEMENT

**Focused beam to inspect from afar :**

- 228\* lumens in VARIO max, 2 lumens in VARIO min.
- Lighting distance: 100\* meters in VARIO max.

\* ANSI FL1 Standard measures



MODE  
INSPECTION

**Wide and uniform beam for comfortable lighting of the work area and hands :**

- 215\* lumens in VARIO max, 6\* lumens in VARIO min.
- Lighting distance: 44\* meters in VARIO max.



MODE  
MANUAL

**Light beam can be rotated 180° (90° upwards and 90° downwards).**

### Energy – Operating time

3 LR03/AAA 1,5V alkaline batteries supplied.

Operating time: 275\* hours (7 hours 50\* in VARIO max).

Battery test mode: indication of the remaining capacity in the batteries (4 levels).

Compatible with **DUOPAK** and RC03/AAA 1.5V rechargeable batteries (not supplied).

### Application – Use

Industrial maintenance - Construction - Craftsmen (plumbing, electrical...) - Automobile repair...

Operating time: -25°C / +50°C.

Can be worn around the chest in pectoral mode.

Placed on a flat surface, with 180° vertical adjustable beam.

### Protection – Safety

IP54: weather resistance (rain, snow, etc.) and dust.

Excellent shock and crush resistance. Fall height: 2 m.

**Security lock on/off: switch-on safety device.**

Electronic protection of the lamp in case of short-circuit or polarity reversal.

Attached battery cap; simple and fast battery changing.

Photobiological risk: Group 2, moderate risk; safely at a distance of 2 meters. Measures according to standard IEC 62471.

Elastic harness with reflective bands visible from the front and back. Mounted as a shoulder strap or around the neck.

### Lamp enclosure

Polyamide housing, resistant to hydrocarbon splashes, corrosive oils and liquids.

Glass in high optical quality polycarbonate, with polyurethane rubber protective coating.

Electrical contacts: stainless steel. Maintenance: rinse the lamp with clear water and dry.

Adjustable harness, hypoallergenic and washable at 30° C.

### Characteristics – Dimensions

Extremely light weight: 155 grams, batteries and handband included.

Dimensions: 62x35x48 mm. Case color : grey.

Customizable on request (color, marking, handband...).

### Accessories (optional)

**DUOPAK**, rechargeable Lithium USB-C battery pack.

### Warranty

Warranty: 5 years.

All products are tested during production and before packaging.